

10/505338

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
28 August 2003 (28.08.2003)

PCT

(10) International Publication Number  
WO 03/071241 A1

(51) International Patent Classification<sup>7</sup>: G01G 3/14

Bekkestua (NO). JENSEN, Geir, Uri [NO/NO]; Wetle-  
sensvei 52, N-0681 Oslo (NO). LUND, Eivind [NO/NO];  
Myrervn. 21, N-0494 Oslo (NO).

(21) International Application Number: PCT/NO03/00068

(22) International Filing Date: 24 February 2003 (24.02.2003)

(74) Agent: BRYN AARFLOT AS; P.O. Box 449 Sentrum,  
N-0104 Oslo (NO).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
20020901 25 February 2002 (25.02.2002) NO

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,  
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): SINTEF  
ELEKTRONIKK OG KYBERNETIKK [NO/NO]; P.O.  
Box 124 Blindern, N-0314 Oslo (NO).


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): WANG, Dag, T.  
[NO/NO]; Myrervn. 19, N-0494 Oslo (NO). BERN-  
STEIN, Ralph, W. [NO/NO]; Nadderudlia 21B, N-1340

[Continued on next page]

(54) Title: SPRING SCALE



(57) Abstract: A spring scale, in particular for weighing loads in the  $\mu\text{g}$ -mg range, comprises a load platform suspended by at least three flexural springs in a surrounding frame, and has bridge-connected strain gauges arranged for measuring strain on one side of the flexural springs. The flexural springs extend in succession along substantially the whole periphery of the load platform in a gap between the load platform and the inner edge of the frame, and an attachment spot on the load platform for every flexural spring is arranged substantially directly opposite or past an attachment spot on the inner edge of the frame for a next flexural spring in the succession of springs. Preferably, the spring scale is made in one piece, and manufactured by means of semiconductor process technology.

WO 03/071241 A1